

 **BELLTEC** *Industries, Inc.*

**Belltec H Series Auger Drives
5 Year Warranty**



Drill holes fast, where others fail.

Belltec H Series Auger Drives

The **Belltec H Series** hydraulic auger drives are available in three models for systems operating between 10 and 35 GPM and 2000 to 3000 PSI. The H Series planetary outperforms and has heavier components than any of its competitors. First tubular frame on the market with the largest and strongest cradle. Mounting frame mounts to all modern skid loaders with the universal attach system. The **H Series** units are ideal for the toughest drilling applications from dirt to solid rock and concrete when paired with the correct H Series auger.

No Case Drain Hoses Required

Features:

- Heaviest in Class Planetary Gearbox with No Snaps Rings
- Heavy Duty Nut Prevents Shaft Pull Out
- Heavy Duty Motors with High Pressure Seal
- Heavy Duty Hexagon Housing
- 2" Hex Output Shaft



Exclusive bolt on 2" hex output shaft significantly reduces costly down time and repair costs if a shaft is bent or broken



Extra large step with non-skid for entering and exiting skid loaders and owners manual canister so the manual stays with the unit at all times



Large cradle holds drive in place and allows for better visibility while in transport position

MODEL H-200		ORDER NUMBER 113001	
MAXIMUM OUTPUT TORQUE		2000 FT-LBS	
RECOMMENDED FLUID FLOW		10-20 GPM	
MAXIMUM PRESSURE-CONTINUOUS		3000 PSI	
RECOMMENDED MAX AUGER DIA-ROCK		24 INCHES	
RECOMMENDED MAX AUGER DIA-DIRT		30 INCHES	
OUTPUT SPEED		OUTPUT TORQUE	
FLOW	SPEED	PRESSURE	TORQUE
GPM	RPM	PSI	Lb-Ft
10	48	2000	1339
12	55	2200	1480
14	64	2400	1607
16	73	2600	1740
18	82	2800	1874
20	92	3000	2008

MODEL H-300		ORDER NUMBER 113014	
MAXIMUM OUTPUT TORQUE		3000 FT-LBS	
RECOMMENDED FLUID FLOW		15-30 GPM	
MAXIMUM PRESSURE-CONTINUOUS		3000 PSI	
RECOMMENDED MAX AUGER DIA-ROCK		36 INCHES	
RECOMMENDED MAX AUGER DIA-DIRT		36 INCHES	
OUTPUT SPEED		OUTPUT TORQUE	
FLOW	SPEED	PRESSURE	TORQUE
GPM	RPM	PSI	Lb-Ft
15	47	2000	1958
18	56	2200	2066
22	68	2400	2350
26	81	2600	2546
28	87	2800	2742
30	93	3000	2937

MODEL H-350		ORDER NUMBER 113016	
MAXIMUM OUTPUT TORQUE		3000 FT-LBS	
RECOMMENDED FLUID FLOW		15-30 GPM	
MAXIMUM PRESSURE-CONTINUOUS		3000 PSI	
RECOMMENDED MAX AUGER DIA-ROCK		36 INCHES	
RECOMMENDED MAX AUGER DIA-DIRT		36 INCHES	
OUTPUT SPEED		OUTPUT TORQUE	
FLOW	SPEED	PRESSURE	TORQUE
GPM	RPM	PSI	Lb-Ft
20	51	2000	2388
24	62	2500	2985
26	67	3000	3582
28	72		
30	77		
35	90		



P. O. BOX 849
 MOBILE, ALABAMA 36601 USA
 ☎ +1 251 438 9881
 📄 +1 917 464 7982 OR +1 347 710 1058
 email: mobile@opico.com Web: www.opico.com