



BLUELINE PEANUT DRYERS

Standard Features

Every Blueline Dryer features aerodynamic, stainless steel burners for long life and greater reliability, and are available for use with LP vapor or natural gas. Burner and fan control power are separately derived from transformers inside the control panel.

STANDARD FEATURES

Standard Features

Blueline's safety features insure burner power is unavailable until power has been supplied to fan

Purge timer delays ignition for 15 seconds, allowing fan to disperse any accumulated gas

All controls and control wiring are protected by internal circuit breakers

High limit switch interrupts power for ignition and gas if internal temperature exceeds 200°F

Gas solenoid valve closes upon ignition failure or flameout

The fan motor is protected by a magnetic starter with quick-trip overload heaters or solid state overload

12-hour timer, with HOLD feature, to shut down the dryer at a predetermined time when desired

All metal surfaces primed and painted with industrial enamel

The cast aluminum propeller blade is non-overloading and precisely balanced for maximum airflow per kilowatt

Each unit is thoroughly checked and then test-fired to ensure proper performance

50 hertz models for LP Vapor or natural gas are available for export markets

Specifications and product details are subject to change without notice



SEMI-TRAILER PEANUT DRYERS

Standard Features

Over 2,500 semi-trailer peanut dryers in operation in the US

Increased production

Lower operating costs

Higher peanut quality

Dryers for PUP trailers available

More uniform drying than traditional wagons

Custom designed dryers available

TRADITIONAL WAGON PEANUT DRYERS

Standard Features

Swing arm and skid mount styles available

Dryers for 8.5 meter, 6.4 meter & 4.2 meter wagons available

Dual and single wagon dryers available

Custom designed dryers available



BLUELINE		FAN SPECIFICATIONS				AIR VOLUME AT INDICATED STATIC PRESSURE						BURNER OUTPUT (kcal/HR)	
MODEL #	USAGE	DIA. IN	HP	RPM	BRAKE HP	2 CM	3 CM	4 CM	5 CM	7 CM	8 CM	STANDARD	OPTIONAL
4207	SKID OR ARM	61 CM	7	3,450	6.03	12,000	11,200	10,300	9,450	8,500	7,400	15,382.028 - 126082.2	88,257.54 - 327,813.73
2712	1 OR 2-4.27 M TRAILERS	69 CM	12	3,450	10.7	17,320	16,550	15,780	14,980	14,100	13,100	88,257.54 - 327,813.73	88,257.54 - 504,328.81
3208	1-8.53 M TRAILER	82 CM	7.5	1,750	8.3	22,000	20,200	17,500	9,700	6,100	3,500	88,257.54 - 504,328.81	
3610	2-6.41 M TRAILER	92 CM	10	1,750	9.9	26,000	22,420	20,400	14,000	9,000	9,000	88,257.54 - 504,328.82	
3610-C	1-8.53 M SEMI PUP	92 CM	10	1,750	9.9	26,000	22,420	20,400	14,000	9,000	5,500	88,257.54 - 504,328.83	
3825	1-12.19 M OR 13.72 M TRAILER	97 CM	25	1,750	27	41,510	38,475	35,235	34,200	32,850	32,850	88,257.54 - 504,328.84	
3830	1-13.72 M OR 14.63 M TRAILER	97 CM	30	1,750	32.1	43,320	40,050	37,890	36,750	35,200	35,200	88,257.54 - 504,328.85	

Opico

P.O. Box 849 • Mobile, Alabama 36601, USA
 T + 1.251.438.9881 | F+1.347.710.1058
 mobile@opico.com | www.opico.com



opico.com